

VESI-PAULI OY

Delivers filter cartridges in the dimensions and densities desired by the customer.



Our product range includes braided nylon, polyester and polypropylene filters and “Meltdown” filter cartridges.

REPRESENTATION OF KSH NOZZLES IN FINLAND

Polypropylene 90°

RO front filter 60°

Nylon 169°

Polyester 120° (district heat)

Vacuum salt tablets for water softening 1 000 kg / pallet

Water softening filter cation resin



+ 358 9 6899 5415

posti@vesipauli.fi

www.vesipauli.fi

Puurtajankatu 28 F

04440 Järvenpää

FINLAND

+358 500 974 304 Tobias Takko

+358 500 609 981 Rainer Takko

SAMPLE COOLER VP-6 and VP-12

	VP-6	VP-12
Material	AISI 316	
Design pressure		
Shell	10 bar	
Coil	180 bar	
Design temperature		
Shell	60° C	
Coil	550° C	
Media		
Shell	Water	
Coil	Steam/Condensate	
Volume		
Shell	1 dm ³	2 dm ³
Coil	0,08 dm ³	0,15 dm ³
Weight	5 kg	7 kg

Cooling water inlet

Min. temperature 18°C

Cooling water outlet

Max. temperature 60°C

Sample outlet 25°C

Cooling water

Max. flow 46 l/min



SAMPLE CATION EXCHANGER NKI-600

Cation exchanger removes ammonia ions from sample before conductivity measurement so that other impurities in sample can be measured without ammonia distortion in the sample.

Sample flow max	1 l/min
Design pressure	10 bar
Design temperature	50°C

